

## Ear Plug Uncorded 26db

EPDB26 Bullet Ear Plug Uncorded 26db

### Eagle Uncorded Ear Plugs 26db

Ear plugs with a 26 dB noise reduction rating and bullet shape design are an effective way to protect your hearing in noisy environments. These ear plugs are made from soft foam that conforms to the shape of your ear canal, providing a comfortable and secure fit. The bullet shape design makes them easy to insert and remove, and they are ideal for use in construction sites, factories, and other loud environments. With a noise reduction rating of 26 dB, these ear plugs can help to prevent hearing damage and reduce the risk of noise-induced hearing loss. They are also disposable, making them a convenient and cost-effective hearing protection solution.



#### Key Features

1. Provides 27dB noise reduction for effective hearing protection
2. The bullet shape design makes them easy to insert and remove,
3. Ideal for use in noisy environments
4. AS/NZS1270 class 5 26db
5. Compliant with safety standards for hearing protection equipment

#### Recommended For

- Medical
- Industrial
- Construction
- Sleeping



AUSTRALIAN STANDARD  
AS/NZS 1716  
BENCHMARK

## Ear Plug Uncorded 26db

EPDB26 Bullet Ear Plug Uncorded 26db

### ATTENUATION TABLE

Technical Specifications for: EPDB26

Attenuation Data (tested in accordance with AS/NZS 1270:2002)

								Class	SLC80
Frequency Hz	125	250	500	1000	2000	4000	8000	5	26
Mean	27.9	24.4	28.2	30.3	35.8	40.6	40.2		
Sid.Dev.	8.7	7.2	8.1	7.3	5.3	6.6	6.6		
Mean-SD	19.1	17.2	20.1	23.1	30.6	34.0	33.6		

Hearing protection class 5 to AS/NZS 1270:2002

When selected use and maintained as specified in AS/NZS 1269, this protector may be used in noise levels up to 110 dB (A) assuming an 85dB(A)

UNDER AS/NZS 1270:2002 THE FOLLOWING CLASS SYSTEM IS USED FOR SELECTION OF HEARING PROTECTORS

Class	Average exposure dB A over 8 hours	SLC80dB(A) range
1	Less than 90	10 to 13
2	90 to less than 95	14 to 17
3	95 to less than 100	18 to 21
4	100 to less than 105	22 to 25
5	105 to less than 110	26 or greater